


PASS STANDARD TOOLS OBLONG

| | SIZE | DIM. D | PART-NO. |
|----------------------|-----------------------------|-----------------------------|----------|
| PUNCH (H-PM®) | | | |
| | 0 | 1,00 - 6,00 | 107A04C |
| | 0 | 6,01 - 10,50 ^(*) | 107B04C |
| | 1 | 1,00 - 30,50 | 101114C |
| | 2 | 30,51 - 40,00 | 101214C |
| | 2 | 40,01 - 50,80 | 101224C |
| | 2 | 50,81 - 60,00 | 101234C |
| | 2 | 60,01 - 72,00 | 101244C |
| | 2 | 72,01 - 76,20 | 101254C |
| | Reinforced | 1,00 - 30,50 | 108114C |
| | Reinforced | 30,51 - 40,00 | 108124C |
| STRIPPER | | | |
| | 2 | 1,00 - 78,00 | 112214C |
| DIE (HWS) | | | |
| | 1 ⁽²⁾ | 1,00 - 32,00 | 106114C |
| | 2 ⁽³⁾ | 32,01 - 77,00 | 106214C |
| | 1 reinforced ⁽²⁾ | 1,00 - 32,00 | 109114C |
| | 2 reinforced ⁽³⁾ | 32,01 - 42,00 | 109224C |
| | 2 reinforced ⁽³⁾ | 42,01 - 62,00 | 109234C |



Additional costs:

PUNCH

Punches with shear (WT / DOWT / etc.) -> see page 56

^(*) Smaller 6,00 mm

Cutting part under 1,00 mm

X3-PM quality -> see page 68

STRIPPER

PU coating for low-scratch material handling

DIE

⁽²⁾ H-PM® quality

⁽³⁾ H-PM® quality

Slug-stop version (negative cutting)

Additional keyway

Brush version for low-scratch material handling

X8-PM quality -> see page 68

Cross references:

PUNCH

| | |
|---|---------|
| Fully guided punch | 15 |
| Slitting tools for slittings close to embossing | 30 - 31 |
| Adjusting rings | 34 |
| Punch chuck | 35 |
| ps:®passfit - explanation and additional costs | 40 |
| Additional costs for coating | 54 |
| Polished cutting part | 55 |

STRIPPER

| | |
|-------------------|----|
| Spare parts | 52 |
| Push-out stripper | 53 |
| PU stripper | 65 |

DIE

| | |
|---------------------------------------|----|
| Adapter rings | 35 |
| Compensating rings | 38 |
| RTC cartridge and die carrier | 41 |
| Die clips | 52 |
| Slug-snap version (for slug-problems) | 57 |

see page