

RAE

ASYMMETRICAL 3-ROLLS BENDING MACHINE



Capacity : 1,5 – 3 mm – Length : 1-2 m

Standard Equipment

- ✓ Built in cast iron on very rigid profile frame
- ✓ Self-lubricating bearings
- ✓ Pre-bending roll movement by handwheel, complete with accurate position indicator
- ✓ Top and pinch roll driven by electromechanical geared motor with brake
- ✓ Double safety foot pedal for roll rotation
- ✓ Easy to open by removal of parts

Options

- ✓ Heat treatment of rolls (hardening HF for hardness 50/60 HRC)
- ✓ Help device for occasional cone bending



CAPACITIES

All the technical information for our RAE product can be found in our web site by scanning this flash code. Look at the photo gallery or watch the video ...



| 3 Rolls | Capacities | | Rolls diameter (mm) | Electric Power (kw) | Dimensions (Length x width x height) (mm) | Weight (kg) |
|----------|---------------------|-------------------|------------------------|------------------------|---|----------------|
| | Useful rolls length | Maximal thickness | | | | |
| | (mm) | (mm) | | | | |
| RAE 1025 | 1020 | 2,5 | 90 | 1,1 | 1800 x 600 x 1200 | 520 |
| RAE 1030 | 1020 | 3 | 114 | 1,5 | 1800 x 600 x 1200 | 620 |
| RAE 1520 | 1520 | 2 | 90 | 1,1 | 2300 x 600 x 1200 | 690 |
| RAE 1525 | 1520 | 2,5 | 114 | 1,5 | 2300 x 600 x 1200 | 780 |
| RAE 2015 | 2020 | 1,5 | 90 | 1,1 | 2800 x 600 x 1200 | 850 |
| RAE 2020 | 2020 | 2 | 114 | 1,5 | 2800 x 600 x 1200 | 940 |

* Technical capacities are given for Steel S 235 (Yield Strength 240 N/mm²)